



SignBOX II

LED illumination for single or double-sided sign boxes


Easy to install—flexible and firm—SignBOX™ II creates the perfect grid of light for optimum even illumination. Designed for new or retrofit sign cabinets with depths over 125 mm. Available in single-sided and double-sided options.

- 6500 K is now 17% brighter
- Bright, even illumination
- Illuminates 125 mm from face
- Mounted on flexible straps for easy installation
- Constant Current Technology (CCT)



Specifications


Part number	Single-sided	6500 K	701946-6WS201
	Single-sided	5000 K	701946-5WS201
	Double-sided	6500 K	701946-6WD201
	Double-sided	5000 K	701946-5WD201
Dimensions L × W × H	216 mm × 26 mm × 8 mm 60 modules per 6,1 m chain		
Viewing angle	120°		
LEDs per module	Single-sided	3	
	Double-sided	6	
Modules per meter	10		
Coverage per row	300 mm		
Optimal light throw	125 to 300 mm from face		
Operating temperature	-40° C to +70° C		
Protection class	IP66		
Special feature	Cutttable in 100 mm increments		
Power per module	Single-sided	0,90 W	
	Double-sided	1,80 W	
Efficacy	6500 K	117 lm/W	
	5000 K	100 lm/W	
Power capacity	Per SloanLED 60 W 12 VDC power supply		
	Single-sided	60 modules	
	Double-sided	30 modules	
Fastening	Clamps with mechanical fasteners		
Packaging	60 modules per carton, 16 clamps included		
Colour temperatures	6500 K, 5000 K		
Lumens per module	Single-sided	6500 K	105
	Single-sided	5000 K	90
	Double-sided	6500 K	210
	Double-sided	5000 K	180



SignBOX II

LED illumination for single or double-sided sign boxes

Specifications *cont'd*



Mounting hardware	Bracket	Bag of 10	401309-10
	Clamp	Bag of 16	410155-16
	Coupler	Bag of 10	401330-10

