



# BendLUX

## Low-profile, flexible strip lighting

BendLUX LED strip lighting system is the very thin, flexible solution for illuminating routed acrylic block letter, shallow channel letter, and back-lit halo letter applications. Strips are snappable every 45 mm with jumpers for easy flat bends and connections. Slim and versatile, sign builders will quickly discover how easy BendLUX strips install to fit the contours of narrow or shallow letters.

- Bendable in both flat and radial directions
- Easy to mount on back or return of channel letter
- Snappable every 45 mm with jumpers in place for easy flat bends and connections
- Constant Current Technology (CCT)

### Specifications

<b>Part number</b>	701960-6WS241
<b>Dimensions L × W × H</b>	610 mm × 8 mm × 3 mm
<b>Viewing angle</b>	120°
<b>LEDs per section</b>	3
<b>Lumens per strip</b>	365
<b>Nominal colour temperature</b>	6500 K
<b>Minimum radial bend radius</b>	25 mm
<b>Operating temperature</b>	-40° C to +70° C
<b>Special features</b>	Snappable every 45 mm Jumpers between sections for easy flat bends and connections
<b>Power</b>	0,3 W per section, 4,2 W per strip
<b>Efficacy</b>	85 lm/W
<b>Power capacity</b>	12,5 strips per SloanLED 60 W 12 VDC power supply
<b>Fastening</b>	Peel-n-stick
<b>Packaging</b>	12 strips per box
<b>Product warranty</b>	5-year limited

