




PosterBOX

Side illumination for shallow or narrow cabinets

PosterBOX™ features FanFlare™ technology that directs the light across the sign face with bright, even illumination. Designed for single-sided and double-sided sign boxes, PosterBOX can be used for new or retrofitted signs replacing fluorescent.



- Easily illuminates double-sided cabinets with 100-150 mm depths
- Side mounted module
- FanFlare lens technology projects light in a fan pattern to evenly illuminate sign face
- Constant Current Technology (CCT)

Specifications



FlareShield™ on module

Part number	White (6500 K)	701946-CWPBM
	White (5000 K)	701946-NWPBM
Dimensions L × W × H	220 mm × 44 mm × 23 mm	
LEDs per module	3	
Light throw	1,2 m	
Module spacing	Cabinet depth	Center-to-center
	≤10 cm	30 cm
	>10 cm to ≤20 cm	45 cm
Operating temperature	-40° C to +70° C	
Protection class	IP66	
Special feature	FanFlare lens technology	
Power per module	6,7 W	
Efficacy	82 lm/W	
Power capacity	8 modules per SloanLED 60 W 12 VDC power supply	
Fastening	Peel-n-stick and mechanical	
Packaging	10 modules and FlareShields™ per carton	
Colour temperatures	6500 K, 5000 K	
Lumens per module	550	
Accessory	FlareShield™ (401059) for shallower applications to eliminate hot spots	

Green Signage 

