




VL Plus 2 Whites

Everyday standard face lit solutions

VL Plus 2 LED lighting system is based on proven SloanLED channel letter module design and performance. VL Plus 2 offers a variety of solutions and a wide selection of colour temperatures.

- VL Plus 2 is 25% brighter than VL Plus
- **NEW** VL Plus 2 HB Short is 28% brighter than VL Plus 2 Short
- Short available in 5 shades of white
- Constant Current Technology (CCT)



Specifications

Part number	Long	6500 K	701269-6WLA2-MB
	Short	7200 K	701269-7WSA2-MB
		6500 K	701269-6WSA2-MB
		5000 K	701269-5WSA2-MB
		4000 K	701269-4WSA2-MB
		3000 K	701269-3WSA2-MB
		6500 K	701269-6WHA1-MB
	HB Short	6500 K	701269-6WHA1-MB
	Mini	6500 K	701269-6WMA2-MB
Dimensions L × W × H	Long	88 mm × 13 mm × 9 mm	
	Short	60 mm × 13 mm × 9 mm	
	Mini	34 mm × 11 mm × 9 mm	
Viewing angle	120°		
LEDs per module	Long/Short	3	
	Mini	2	
Modules per meter	Long	6,5	
	Short	8	
	Mini	13	
Operating temperature	-40° C to +70° C		
Protection class	IP66		
Power per module	Long/Short	0,54 W	
	Mini	0,42 W	
Efficacy	Long/Short	93 lm/W	
	HB Short	119 lm/W	
	Mini	60 lm/W	
Power capacity	Per SloanLED 60 W 12 VDC power supply:		
	Long/Short	100 modules	
	Mini	128 modules	



VL Plus 2 Whites

Everyday standard face lit solutions

Specifications *cont'd*

Fastening

Peel-n-stick and mechanical

Packaging

5 trays per carton

Long

50 modules per tray

Short

75 modules per tray

Mini

100 modules per tray



Size	Colour temperature	Part number	Lumens per module (nominal)
Long	6500 K	701269-6WLA2-MB	50
Short	7200 K	701269-7WSA2-MB	50
	6500 K	701269-6WSA2-MB	50
	5000 K	701269-5WSA2-MB	50
	4000 K	701269-4WSA2-MB	50
	3000 K	701269-3WSA2-MB	50
HB Short	6500 K	701269-6WHA1-MB	64
Mini	6500 K	701269-6WMA2-MB	25

